

## RD25

### Remote Display for MC Receivers



Specifications	
<b>Compatible Receivers</b>	MCR1w, MCR2w, MCR3w
<b>Radio</b>	Full 2-way Communications, Operation and Security Lock with PAIR'ed Device
<b>Radio Working Radius</b>	30m (100 ft)
<b>Power Options</b>	(2) AA Batteries (internal) 10-30 Vdc (external)
<b>Battery Life (internal)</b>	Up to 20 Hours
<b>Beeper Volumes</b>	Loud = 105 dBA Medium = 95 dBA Low = 75 dBA
<b>LED Grade Indicators</b>	Green = On-Grade Red = High Blue = Low
<b>Automatic Shut Off</b>	30 Min. (if no beam strike or loss of radio link)
<b>Environmental</b>	IP67 Rating (Waterproof, Dustproof)
<b>Weight (without Mount)</b>	323g (11.4 oz.)
<b>Dimensions (without Mount)</b>	6.6" x 3.0" x 1.4"
<b>Operating Temperature</b>	-20°C to +60°C (-4°F to +140°F)
<b>Storage Temperature</b>	-30°C to +70°C (-22°F to +158°F)

Enjoy the convenience of connecting wirelessly to a MCR1w, MCR2w or MCR3w receiver with the RD25.

Also, with the optional RAM mount, you can place the display anywhere in the cab!